

## CREPING BLADE EH

### Carbon steel extra hard

MATERIAL
Carbon steel C = 1,00 %, extra hard
Hardness approx. 51 – 53 HRC (approx. 500 – 532 HB)

STANDARD DIMENSIONS*	
THICKNESS mm (inch)	WIDTH mm (inch)
1.25 (0.050)	90 (3.55), 100 (4), 115 (4.5), 120 (4.75), 125 (4.9), 130 (5.1)
1.5 (0.060)	90 (3.55), 100 (4), 115 (4.5), 120 (4.75), 125 (4.9), 130 (5.1)
* Other widths and thicknesses available on request	

KEY FEATURES
Continuous length to individual specification
Hardened, tempered, plain ground and straight
Bevel from 3° – 90°
Straightness tolerance max. 0.2 mm over 1000 mm
Land of 0.1 mm – 1.0 mm

SUITABLE HOLDERS
Ready to install for all holder systems



**JOH. CLOUTH®**  
A CLOUTH GROUP MEMBER

#### Joh. Clouth GmbH

Johann-Clouth-Straße 1-5  
D-42499 Hückeswagen  
Phone: + 49 2192 853-0  
E-Mail: [sales@clouth-group.com](mailto:sales@clouth-group.com)