

## DURADA®-DT

### Doctor Blade from advanced polymer material

MATERIAL	
Multi-layer fiberglass fabric structure with thermoplastic polymer matrix and ceramic coating at tip, very wear-resistant	
MATERIAL COLOUR	 beige
LOGO COLOUR	 black
BENDING STRENGTH	up to 250 N/mm <sup>2</sup>
TEMPERATURE RESISTANCE IN CONTINUOUS USE	180°C
CHEMICAL RESISTANCE	very good
WATER ABSORPTION	none

STANDARD DIMENSIONS*	
THICKNESS mm (inch)	WIDTH mm (inch)
1.5 (0.060)	75 (3)
* OTHER WIDTHS AND THICKNESSES AVAILABLE ON REQUEST	

KEY FEATURES
CONTINUOUS LENGTH TO INDIVIDUAL SPECIFICATION
DOUBLE BEVEL
Bevel Angle 20°
Without rebate; groove to customer requirements
Wear indicator: Ceramic layer is an indicator

RIVETING
Ready to use for all standard holder systems with appropriate rivets.



**JOH. CLOUTH®**  
A CLOUTH GROUP MEMBER

#### Joh. Clouth GmbH

Johann-Clouth-Straße 1-5

D-42499 Hückeswagen

Phone: + 49 2192 853-0

E-Mail: sales@clouth-group.com