

COATER BLADES IN STAINLESS STEEL

Coater Blade in stainless steel

MATERIAL
Stainless steel (18-8) 1.4310
Hardness approx. 46 – 48 HRC (approx. 437 – 461 HB)

STANDARD DIMENSIONS*	
THICKNESS mm (inch)	WIDTH mm (inch)
0.3 (0.012)	76.2 (3), 84 (3.3), 100 (4)
0.381 (0.015)	76.2 (3), 84 (3.3), 100 (4)
0.4 (0.016)	76.2 (3), 84 (3.3), 100 (4)
0.457 (0.018)	76.2 (3), 84 (3.3), 100 (4)
0.5 (0.020)	76.2 (3), 84 (3.3), 100 (4)
* Other widths and thicknesses available on request	

KEY FEATURES
Continuous length to individual specification
Blank ground and polished, even and straight
Bevel from 3° – 90°
Straightness tolerance max. 0.05 mm over 1000 mm
Quick-Start Bevel
Land of 0.02 mm – 0.55 mm depending on material thickness

SUITABLE HOLDERS
Ready to install for all holder systems with and without riveting



JOH. CLOUTH®
A CLOUTH GROUP MEMBER

Joh. Clouth GmbH

Johann-Clouth-Straße 1-5

D-42499 Hückeswagen

Phone: + 49 2192 853-0

E-Mail: sales@clouth-group.com